



US006286417B1

(12) **United States Patent**  
**Bichsel**

(10) **Patent No.:** **US 6,286,417 B1**  
**(45) Date of Patent:** **Sep. 11, 2001**

(54) **DRUM COOKER**

(76) **Inventor:** **Rudolf Bichsel**, Gyrisbergstrasse 124,  
 CH-3400 Burgdorf (CH)

(\*) **Notice:** Subject to any disclaimer, the term of this  
 patent is extended or adjusted under 35  
 U.S.C. 154(b) by 0 days.

3,135,668 \* 6/1964 Wesson ..... 134/132  
 3,484,360 \* 12/1969 Sandrock ..... 366/234  
 3,760,714 \* 9/1973 Lortz ..... 99/404  
 4,203,358 5/1980 Vogt .  
 4,335,649 6/1982 Velasco, Jr. et al. .  
 4,410,553 \* 10/1983 McGinty ..... 99/348  
 4,906,104 \* 3/1990 Nishise et al. .... 366/322  
 5,329,842 \* 7/1994 Zittel ..... 99/348  
 5,429,041 \* 7/1995 Zittel ..... 99/470 X

(21) **Appl. No.:** **09/658,478**

(22) **Filed:** **Sep. 8, 2000**

**Related U.S. Application Data**

(63) Continuation of application No. PCT/EP99/00796, filed on  
 Feb. 6, 1999.

(51) **Int. Cl.<sup>7</sup>** ..... **A23L 1/00; A23L 3/00;**  
**A47J 27/00; A47J 37/12; A23N 12/00**

(52) **U.S. Cl.** ..... **99/330; 99/348; 99/352;**  
**99/355; 99/409; 366/101; 366/220**

(58) **Field of Search** ..... **99/325, 330, 348,**  
**99/352-355, 360, 365, 403-409, 450, 470,**  
**483, 485, 486, 487, 516, 517, 534, 536,**  
**477-479, 443 R, 443 C; 366/81, 91, 101-107,**  
**220-236**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,231,002 \* 6/1917 Steere ..... 134/132  
 1,290,396 \* 1/1919 Steere ..... 134/132  
 1,806,957 \* 5/1931 Stocking ..... 134/132  
 2,166,197 \* 7/1939 Schaub ..... 366/322  
 2,314,871 \* 3/1943 DeBack ..... 134/65  
 2,909,872 \* 10/1959 Kearney et al. .... 134/132

**FOREIGN PATENT DOCUMENTS**

06062968 3/1994 (JP) .

**OTHER PUBLICATIONS**

XP-002108205-Rotary Cereal Cooker, 1999; 1-page.

\* cited by examiner

*Primary Examiner*—Timothy F. Simone

(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce,  
 P.L.C.

(57) **ABSTRACT**

A drum cooker for cooking granular products comprises a vessel mounted to rotate about an axis. At least two nozzle groups are provided opening into said vessel. One of said nozzle groups is arranged in that it opens into a first area of said vessel covered by that granular product. A second nozzle group opens into a second area of said vessel not covered by said granular product. For enhancing the quality of the cooking process, a control means is provided for supplying said gaseous heat-carrying medium at any time to said nozzle group only that opens into that first area covered by said product.

**6 Claims, 2 Drawing Sheets**

